



FPN7840 Series



FPSI201



FPSI202

FPN7840 GE Astrodome® Replacement Controls

Direct replacement for use in Astrodome-type lighting fixtures.

Specifications

Photocell:	Silicon Sensor
Switch Type:	SPST-NC (single-pole, single-throw, normally closed) electromagnetic relay
Housing:	UV-resistant, high-impact, polypropylene with clear UV-stabilized window
Turn-On:	1 footcandle (fc)
Turn-On/Off ratio:	1.5:1
Rated Life:	5,000 operations minimum at rated load
Temperature Range:	- 40° to + 70°C - 40° to + 158°F
Dimensions:	3.25" Dia.; 2.0" H
Wire Length:	24" cable

SI200 Series Screw In Controls

Specifications

Photocell:	Silicon Sensor
Housing:	Polycarbonate
Operating Level:	3 to 10 footcandles (fc)
Temperature Range:	- 40° to + 70°C - 40° to + 158°F
Power Consumption:	0.5Watts
Screw Shell:	Medium base

Ordering Information

Model	Line Voltage	Load Rating HID Ballast
FPN7841	105-130	1800VA
FPN7842	105-305	1800VA

® Registered trademark of General Electric Company

Ordering Information

Model	Line Voltage	Load Rating
FPSI201	120V	150W incandescent
FPSI202	120V	150W incandescent

Not recommended for LED installations