

Stand-Alone Dimming Controls - Field Adjustable

Dimulator™ 4
Patent Pending

*Field
Adjustable*



Lights too Bright—Dim All Night



Dimming controls include proprietary Bat Eye Technology circuit
Energy savings • Reduced service calls • Only reacts to sunlight

Dimulator 4.0

Unsurpassed construction, electrical, process, and environmental protections make the **Dimming Control** the highest grade twiststock photocontrol on the market today. The stand alone unit is made to work with the **ANSI C136.41** receptacle and will provide dimming of LED fixtures.

- No Network Required
- Immediate Energy Savings
- Extend the life of the Fixture
- Works on any Dimmable LED Fixture
- Long Life Photocontrol features
- AM Ramp up to Full Brightness
- Robust Surge Protection - 40k Amp MOV/640Joule
- Light Diagnostic on Installation

Specifications

Operating Voltage Range:	105-305 VAC, 50/60 Hz	
Load Rating	1,000W/1,800 VA	15 Amp relay tested to 15,000 operations on maximum available LED or Induction load
Operating Temperature	-40°C to +70°C	(-40°F to +158°F)
Surge Protection	40,000 Amps	Single 640 Joule MOV
Power Consumption	<0.5 Watts	@ 120 V
Dielectric Strength	5,000 Volts	Between current carrying parts

Ordering Information

Model	Description
DIM-4	105-305 VAC, 50/60 Hz, Adjustable Control - Black Cover
DIM-4 cUL	105-305 VAC, 50/60 Hz, Adjustable Control - Blue Cover