



The Real Score LED Photocontrol

Designed to meet or exceed the life expectancy of LED fixtures. The Score Control has the same proven electronic circuit as our highly reliable electronic photocontrols. Upgraded materials and environmental protections were added to The Real Score product to achieve a 20 year expected life.

Now that's a MOV

To protect the electronic components (and the LED Fixture) for 20 year expected life, The Score Control RMS clamping voltage is just above line voltage. Our 40,000 amp MOV can be expected to protect against repeated spikes/surges over a 20 year period, where smaller MOVs would not.

Unsurpassed Features for Ultra Long Life

Unsurpassed construction, electrical, process, and environmental protections make the TRS Series the highest grade twistlock photocontrol on the market today. No aspect of design was overlooked, thus eliminating any potential weak point. It is designed to meet or exceed the life expectancy of LED and Induction lights. The TRS is the best value photocontrol available.

Ordering Information

Specifications

Load Rating:	1,000W/1,800 VA 15 Amp relay tested to 15,000 operations at 1,000 watts. AIR GAP load break has no voltage leakage
Operating Temperature:	-40°C to +70°C (-40°F to +158°)
Surge Protection:	40,000 Amps 640 Joule MOV
Power Consumption:	<0.5 Watts @ 120 V
Dielectric Strength:	5,000 Volts Between current carrying parts

Operating Voltage

Load Rating:	1000 Watt tungsten, 1800 VA
Moisture Resistance:	100% RH
Operating Light Levels:	+/- 0.1 fc. from specified turn-on level 1:1.5 Average turn-on to turn-off ratio
Photosensor:	Proprietary Encapsulate Bat Eye Technology circuit eliminates unintentional operation of LED fixtures, only reacts to sunlight, avoiding fixture cycling, reducing service calls. The sensor has no drift and is consistent over the service life.
Dielectric Strength:	5,000 Volts between any current carrying part
Ambient Temperature Range:	-40°C to +70°C (-40°F to + 158°F)

TRS - 2 - FO

Model # *TRS-2 (105-305V) TRS-3 (347V) TRS-4 (480V) TRS-2-CUL [®] (105-305V)	Surge Protection _ (1) 640Joule MOV, 40,000 Amps (Standard)	Relay Option _ 15 Amp-15,000 operations (Standard)	Fail Mode _ Fail ON (Standard) FO Fail OFF	Color _ Black (standard) _ CUL [®] Cover Blue- <i>Other Colors Available upon Request</i>
--	---	--	--	--

Other configurations available-Please contact Customer Service at 508-821-1597

Note: No substitution for cUL units

The information in this document is provided for informational use only and is subject to change without notice.

© 2020 by Sunrise Technologies, Inc. All rights reserved.