

FPN250 Series

FPN250 Series

The FPN250 Series is a flat-surface mounting relay which provides a combination of reliable contactor and sturdy internal lightning arrester and high dielectric strength for substantial protection against surges and overloads.


The FPN270 Series is a relay/receptacle/mounting bracket assembly for flat-surface or pole mounting. In addition to surge protection, this lightning relay offers the flexibility of easy installation and replacement of photoelectric controls through a receptacle/relay combination for outdoor mounting.

Application

Weatherproof NEMA 3R Lighting Relays. Two mounting options to raise the switching capacity of photoelectric controls or other switching devices. These relays are used for centralized switching of several lighting an/or luminaires from a single point while providing additional surge and overload protection. Ideal for commercial and industrial applications where there is a need to control multiple fixtures wired to a 30 amp lighting contactor.

Ordering Information

Model	Line Voltage	SPST Contacts	Load Rating	
			Tungsten	Ballast
FPN251A	120	N.O.	3000W	2400VA
FPN252A	120	N.C.	3000W	2400VA
FPN271	120	N.O.	3000W	2400VA
FPN272	120	N.C.	3000W	2400VA



FPN270 Series

Model FPN251A

Outdoor relay for flat, vertical surface mounting with lightning arrester, normally open contacts.

Dimensions: 4.5" H: 3" W: 3" D

Model FPN252A

Same as Model FPN251A, except reverse contacts, normally closed contacts.

Dimensions: Same as Model FPN251A

Model FPN271

Receptacle and relay combination for outdoor weatherproof mounting. Flat surface, normally open contacts.

Dimensions: 7"H: 3"W: 3"D

Model FPN272

Same as Model FPN271 except reverse contacts, normally closed contacts.

Dimensions: Same as Model FPN271

The information in this document is provided for informational use only and is subject to change without notice.

© 2020 by Sunrise Technologies, Inc. All rights reserved.